


90° LED ASSEMBLIES

Locating Pin Assemblies



- Extra PCB Retention for Secure and Pre-Solder Handling
- Wide Selection of Colors and Brightness
- Other Color Combination Available

H125C-LP Series

T-1 (3mm) Locator Pin Assembly.

LED Assy. No.	Peak Wave Length	Emitted Color	Lens Appearance	Abs. Max. Rating	Electro-Optical Data @20mA			Viewing Angle 2 θ 1/2 (deg)	LED P/N	
					If (mA)	Vf (V)				Iv (mcd)
						TYP	MAX			
H125CBWD-LP	430	BLUE	DIFFUSED	20	4.0	4.5	20.0	45	3BWD	
H125CGD-LP	565	GREEN	DIFFUSED	20	2.2	2.6	30.0	45	3GD	
H125CYD-LP	585	YELLOW	DIFFUSED	20	2.1	2.6	20.0	45	3YD	
H125CHD-LP	635	HE RED	DIFFUSED	20	2.0	2.6	30.0	45	3HD	
H125CRD-LP	655	RED	DIFFUSED	20	1.7	2.0	6.0	45	3RD	
H125CSRDL-LP	660	SUPER RED	DIFFUSED	20	1.7	2.6	90.0	45	3SRD	
Low Current					Data @2mA					
H125CGDL-LP	565	GREEN	DIFFUSED	2	1.9	2.2	6.0	45	3GDL	
H125CYDL-LP	585	YELLOW	DIFFUSED	2	1.9	2.2	4.0	45	3YDL	
H125CHDL-LP	635	HE RED	DIFFUSED	2	1.8	2.2	6.0	45	3HDL	
5 Volt					Data @10mA					
H125CGD5V-LP	565	GREEN	DIFFUSED	10	-	5.0	30.0	45	3GD5V	
H125CYD5V-LP	585	YELLOW	DIFFUSED	10	-	5.0	20.0	45	3YD5V	
H125CHD5V-LP	635	HE RED	DIFFUSED	10	-	5.0	30.0	45	3HD5V	

