

TOSHIBA HIGH EFFICIENCY DIODE STACK (HED) SILICON EPITAXIAL TYPE

20DL2C48A, U20DL2C48A, 20FL2C48A, U20FL2C48A

SWITCHING TYPE POWER SUPPLY APPLICATION.

CONVERTER & CHOPPER APPLICATION.

- Repetitive Peak Reverse Voltage : $V_{RRM}=200, 300V$
- Average Output Rectified Current : $I_O=20A$
- Ultra Fast Reverse-Recovery Time : $t_{rr}=35ns$ MAX.
- Low Switching Losses and Output Noise.


Unit in mm

20DL2C48A·20FL2C48A		U20DL2C48A·U20FL2C48A	
	<ol style="list-style-type: none"> 1. ANODE 2. ANODE 3. CATHODE 		<ol style="list-style-type: none"> 1. ANODE 2. ANODE 3. CATHODE
JEDEC	—	JEDEC	—
EIAJ	—	EIAJ	—
TOSHIBA	12-10D1A	TOSHIBA	12-10D2A

MAXIMUM RATINGS

CHARACTERISTIC		SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	20DL2C48A	V_{RRM}	200	V
	U20DL2C48A		300	
	20FL2C48A			
	U20FL2C48A			
Average Output Rectified Current		I_O	20	A
Peak One Cycle Surge Forward Current			100 (50Hz)	A
			110 (60Hz)	
Junction Temperature		T_j	-40~150	°C
Storage Temperature Range		T_{stg}	-40~150	°C

POLARITY



961001EAA2


● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage	20DL2C48A	V _{FM}	I _{FM} = 10A	—	—	0.98	V
	U20DL2C48A						
	20FL2C48A			—	—	1.3	
	U20FL2C48A						
Repetitive Peak Reverse Current		I _{RRM}	V _R = Rated	—	—	50	μA
Reverse Recovery time		t _{rr}	I _F = 2A, di / dt = -50A / μs	—	—	35	ns
Forward Recovery time		t _{fr}	I _F = 1A	—	—	100	ns
Thermal Resistance		R _{th(j-c)}	DC Total	—	—	1.6	°C / W

V_{FM}, I_{RRM}, t_{rr}, t_{fr} : A value of one cell.

MARKING



※1	MARK	20DL2C	TYPE	20DL2C48A, U20DL2C48A
		20FL2C		20FL2C48A, U20FL2C48A
※2	A			
※3	Lot Number			
	<input type="checkbox"/> <input type="checkbox"/> — Month (Starting from Alphabet A) <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> — Year (Last Number of the Cristian Era)			

961001EAA2'

- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

