

# NPN SILICON RF POWER TRANSISTOR

## DESCRIPTION:

The **ASI FMB075** is Designed for


## FEATURES:

- 
- 
- **Omnigold™** Metalization System

## MAXIMUM RATINGS

<b>I<sub>C</sub></b>	10 A
<b>V<sub>CB</sub></b>	60 V
<b>V<sub>CE</sub></b>	35 V
<b>P<sub>DISS</sub></b>	140 W @ T <sub>C</sub> = 25 °C
<b>T<sub>J</sub></b>	-65 °C to +200 °C
<b>T<sub>STG</sub></b>	-65 °C to +150 °C
<b>θ<sub>JC</sub></b>	1.5 °C/W

## PACKAGE STYLE .500 4L FLG



DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B	.125 / 3.18	
C	.245 / 6.22	.255 / 6.48
D	.720 / 18.28	.730 / 18.54
E	.125 / 3.18	
F	.970 / 24.64	.980 / 24.89
G	.495 / 12.57	.505 / 12.83
H	.003 / 0.08	.007 / 0.18
I	.090 / 2.29	.110 / 2.79
J	.150 / 3.81	.175 / 4.45
K		.280 / 7.11
L	.980 / 24.89	1.050 / 26.67

**ORDER CODE: ASI10587**

## CHARACTERISTICS T<sub>C</sub> = 25 °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
<b>BV<sub>CEO</sub></b>	I <sub>C</sub> = 50 mA	35			V
<b>BV<sub>CER</sub></b>	I <sub>C</sub> = 50 mA R <sub>BE</sub> = 10 Ω	60			V
<b>BV<sub>EBO</sub></b>	I <sub>E</sub> = 10 mA	4.0			V
<b>I<sub>CES</sub></b>	V <sub>E</sub> = 28 V			5	mA
<b>h<sub>FE</sub></b>	V <sub>CE</sub> = 5.0 V I <sub>C</sub> = 1.0 A	10		100	---
<b>C<sub>ob</sub></b>	V <sub>CB</sub> = 28 V f = 1.0 MHz			75	pF
<b>P<sub>G</sub></b> <b>η<sub>C</sub></b>	V <sub>CC</sub> = 28 V P <sub>OUT</sub> = 75 W f = 108 MHz	10	65		dB %