


BCD-to-Decimal Decoder Binary-to-Octal Decoder


This decoder is constructed so that an 8421 BCD code on the four inputs provides a decimal (one-of-ten) decoded output, while a 3-bit binary input provides a decoded octal (one-of-eight) code output with D forced to a logic "0". Expanded decoding such as binary-to-hexadecimal (one-of-16), etc., can be achieved by using multiple devices.

- Supply voltage range = 3.0 Vdc to 18 Vdc
- All outputs buffered
- Capable of driving 4 Low Power TTL loads or one LS TTL load over the rated temperature range
- Diode protection on all inputs
- Highest noise immunity at 12V supply

DV4028B




N Suffix
Plastic DIP
AVG-003 Case




D Suffix
Plastic SOP
AVG-004 Case

4028B



PIN 16 = V_{DD}
PIN 8 = V_{SS}

PIN ASSIGNMENT



TRUTH TABLE

INPUT				OUTPUT									
D	C	B	A	Q9	Q8	Q7	Q6	Q5	Q4	Q3	Q2	Q1	Q0
0	0	0	0	0	0	0	0	0	0	0	0	0	1
0	0	0	1	0	0	0	0	0	0	0	0	1	0
0	0	1	0	0	0	0	0	0	0	0	1	0	0
0	0	1	1	0	0	0	0	0	0	1	0	0	0
0	1	0	0	0	0	0	0	0	1	0	0	0	0
0	1	0	1	0	0	0	0	1	0	0	0	0	0
0	1	1	0	0	0	0	1	0	0	0	0	0	0
0	1	1	1	0	0	1	0	0	0	0	0	0	0
1	0	0	0	0	1	0	0	0	0	0	0	0	0
1	0	0	1	1	0	0	0	0	0	0	0	0	0
1	0	1	0	0	0	0	0	0	0	0	0	0	0
1	0	1	1	0	0	0	0	0	0	0	0	0	0
1	1	0	0	0	0	0	0	0	0	0	0	0	0
1	1	0	1	0	0	0	0	0	0	0	0	0	0
1	1	1	0	0	0	0	0	0	0	0	0	0	0
1	1	1	1	0	0	0	0	0	0	0	0	0	0

ABSOLUTE MAXIMUM RATINGS

Maximum ratings are those values beyond which damage to the device may occur.

Symbol	Parameter	Value	Unit
V _{DD}	Supply Voltage (Referenced to V _{SS})	-0.5 to +18.0	V
V _{IN} , V _{OUT}	Input or Output Voltage	-0.5 to V _{DD} +0.5	V
I _{IN} , I _{OUT}	DC Current Into or Out of Any Pin	± 10	mA
P _D	Power Dissipation in Still Air, Derating: 12 mW/°C from 65° to 85°C	500	mW
T _{STG}	Storage Temperature Range	-65 to +150	°C
TL	Lead Temperature, (8 Second Soldering)	260	°C


ELECTRICAL CHARACTERISTICS (Voltages Referenced to V_{SS})

Symbol	Parameter		V _{DD}	Guaranteed Limits							Unit
				-40°C		25°C			85°C		
				Min	Max	Min	Typ	Max	Min	Max	
V _{OL}	Output Voltage V _{IN} =V _{DD} or 0	"0" Level	5.0 10 15	- - -	0.05 0.05 0.05	- - -	0 0 0	0.05 0.05 0.05	- - -	0.05 0.05 0.05	V _{dC}
V _{OH}	V _{IN} = 0 or V _{DD}	"1" Level	5.0 10 15	4.95 9.95 14.95	- - -	4.95 9.95 14.95	5.0 10 15	- - -	4.95 9.95 14.95	- - -	V _{dC}
V _{IL}	Input Voltage (V _O =4.5 or 0.5 V _{dC}) (V _O =9.0 or 1.0 V _{dC}) (V _O =13.5 or 1.5 V _{dC})	"0" Level	5.0 10 15	- - -	1.5 3.0 4.0	- - -	2.25 4.50 6.75	1.5 3.0 4.0	- - -	1.5 3.0 4.0	V _{dC}
V _{IH}	(V _O =0.5 or 4.5 V _{dC}) (V _O =1.0 or 9.0 V _{dC}) (V _O =1.5 or 13.5 V _{dC})	"1" Level	5.0 10 15	3.5 7.0 11	- - -	3.5 7.0 11	2.75 5.50 8.25	- - -	3.5 7.0 11	- - -	V _{dC}
I _{OH}	Output Drive Current (V _{OH} = 2.5 V _{dC}) (V _{OH} = 4.6 V _{dC}) (V _{OH} = 9.5 V _{dC}) (V _{OH} = 13.5 V _{dC})	Source	5.0 5.0 10 15	-3.0 -0.52 -1.3 -3.6	- - - -	-2.4 -0.44 -1.1 -3.0	-4.2 -0.88 -2.25 -8.8	- - - -	-1.7 -0.36 -0.9 -2.4	- - - -	mAdC
I _{OL}	(V _{OL} = 0.4 V _{dC}) (V _{OL} = 0.5 V _{dC}) (V _{OL} = 1.5 V _{dC})	Sink	5.0 10 15	0.52 1.3 4.2	- - -	0.44 1.3 3.4	0.88 2.25 8.8	- - -	0.36 0.9 2.4	- - -	mAdC
I _{IN}	Input Current		15	-	±0.3	-	±0.00001	±0.3	-	±1.0	μAdC
C _{IN}	Input Capacitance	V _{IN} =0	-	-	-	-	5.0	7.5	-	-	pF
I _{DD}	Quiescent Current (Per Package)		5.0 10 15	- - -	20 40 80	- - -	0.005 0.010 0.015	20 40 80	- - -	150 300 600	μAdC

SWITCHING CHARACTERISTICS (C_L=50 pF, T_A=25°C)

Symbol	Characteristics	V _{DD}	Min	Typ	Max	Unit
t _{TLH} , t _{THL}	Output Rise and Fall Time	5.0	-	100	200	ns
		10	-	50	100	
		15	-	40	80	
t _{PLH} , t _{PHL}	Propagation Delay Time,	5.0	-	300	600	ns
		10	-	130	260	
		15	-	90	180	

SWITCHING WAVEFORMS



4028B