

**CMLM0705**

**MULTI DISCRETE MODULE™**

**SURFACE MOUNT**

**SILICON SWITCHING PNP TRANSISTOR**

**AND**

**LOW  $V_F$  SILICON SCHOTTKY DIODE**



**MDM™**  
Multi Discrete Module



**PICOmini™**



**SOT-563 CASE**

# Central™

## Semiconductor Corp.

### DESCRIPTION:

The Central Semiconductor CMLM0705 is a Multi Discrete Module™ consisting of a single PNP Transistor and a Schottky Diode packaged in a space saving PICOmini™ SOT-563 case. This device is designed for small signal general purpose applications where size and operational efficiency are prime requirements.

- Combination: Small Signal Switching PNP Transistor and Low  $V_F$  Schottky Diode.
- Complementary Device: **CMLM2205**

### MARKING CODE: C75

#### MAXIMUM RATINGS (SOT-563 Package): ( $T_A=25^{\circ}\text{C}$ )

Power Dissipation  
Operating and Storage  
Junction Temperature  
Thermal Resistance

SYMBOL		UNITS
$P_D$	350	mW
$T_J, T_{stg}$	-65 to +150	$^{\circ}\text{C}$
$\theta_{JA}$	357	$^{\circ}\text{C/W}$

#### MAXIMUM RATINGS Q1: ( $T_A=25^{\circ}\text{C}$ )

Collector-Base Voltage  
Collector-Emitter Voltage  
Emitter-Base Voltage  
Collector Current

SYMBOL		UNITS
$V_{CBO}$	90	V
$V_{CEO}$	60	V
$V_{EBO}$	6.0	V
$I_C$	600	mA

#### MAXIMUM RATINGS D1: ( $T_A=25^{\circ}\text{C}$ )

Peak Repetitive Reverse Voltage  
Continuous Forward Current  
Peak Repetitive Forward Current,  $t_p \leq 1\text{ ms}$   
Forward Surge Current,  $t_p=8\text{ms}$

SYMBOL		UNITS
$V_{RRM}$	40	V
$I_F$	500	mA
$I_{FRM}$	3.5	A
$I_{FSM}$	10	A

#### ELECTRICAL CHARACTERISTICS Q1: ( $T_A=25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
$I_{CBO}$	$V_{CB}=50\text{V}$			10	nA
$I_{CBO}$	$V_{CB}=50\text{V}, T_A=125^{\circ}\text{C}$			10	$\mu\text{A}$
$I_{CEV}$	$V_{CE}=30\text{V}, V_{BE}=0.5\text{V}$			50	nA
$BV_{CBO}$	$I_C=10\mu\text{A}$	90	115		V
$BV_{CEO}$	$I_C=10\text{mA}$	60			V
$BV_{EBO}$	$I_E=10\mu\text{A}$	5.0			V
$V_{CE(SAT)}$	$I_C=150\text{mA}, I_B=15\text{mA}$		0.113	0.2	V
$V_{CE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$		0.280	0.7	V
$V_{BE(SAT)}$	$I_C=150\text{mA}, I_B=15\text{mA}$			1.3	V
$V_{BE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$			2.6	V
$h_{FE}$	$V_{CE}=10\text{V}, I_C=0.1\text{mA}$	100	205		
$h_{FE}$	$V_{CE}=10\text{V}, I_C=1.0\text{mA}$	100			
$h_{FE}$	$V_{CE}=10\text{V}, I_C=10\text{mA}$	100			
$h_{FE}$	$V_{CE}=10\text{V}, I_C=150\text{mA}$	100		300	
$h_{FE}$	$V_{CE}=10\text{V}, I_C=500\text{mA}$	75	110		

R0 (06-October 2004)


## ELECTRICAL CHARACTERISTICS Q1 (continued)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
$f_T$	$V_{CE}=20V$ , $I_C=50mA$ , $f=100MHz$	200		MHz
$C_{ob}$	$V_{CB}=10V$ , $I_E=0$ , $f=1.0MHz$		8.0	pF
$C_{ib}$	$V_{BE}=2.0V$ , $I_C=0$ , $f=1.0MHz$		30	pF
$t_{on}$	$V_{CC}=30V$ , $V_{BE}=0.5V$ , $I_C=150mA$ , $I_{B1}=15mA$		45	ns
$t_d$	$V_{CC}=30V$ , $V_{BE}=0.5V$ , $I_C=150mA$ , $I_{B1}=15mA$		10	ns
$t_r$	$V_{CC}=30V$ , $V_{BE}=0.5V$ , $I_C=150mA$ , $I_{B1}=15mA$		40	ns
$t_{off}$	$V_{CC}=6.0V$ , $I_C=150mA$ , $I_{B1}=I_{B2}=15mA$		100	ns
$t_s$	$V_{CC}=6.0V$ , $I_C=150mA$ , $I_{B1}=I_{B2}=15mA$		80	ns
$t_f$	$V_{CC}=6.0V$ , $I_C=150mA$ , $I_{B1}=I_{B2}=15mA$		30	ns

## ELECTRICAL CHARACTERISTICS D1 ( $T_A=25^\circ C$ )


$I_R$	$V_R=10V$		20	$\mu A$
$I_R$	$V_R=30V$		100	$\mu A$
$BV_R$	$I_R=500\mu A$	40		V
$V_F$	$I_F=100\mu A$		0.13	V
$V_F$	$I_F=1.0mA$		0.21	V
$V_F$	$I_F=10mA$		0.27	V
$V_F$	$I_F=100mA$		0.35	V
$V_F$	$I_F=500mA$		0.47	V
$C_T$	$V_R=1.0V$ , $f=1.0MHz$		50	pF

## SOT-563 - MECHANICAL OUTLINE



SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.004	0.007	0.10	0.18
B	0.008		0.20	
C	0.022	0.024	0.56	0.60
D	0.059	0.067	1.50	1.70
E	0.020		0.50	
F	0.061	0.067	1.55	1.70
G	0.047		1.20	
H	0.006	0.012	0.15	0.30

SOT-563 (REV: R0)



MARKING CODE: C75

## LEAD CODE:

- 1) EMITTER Q1
- 2) BASE Q1
- 3) CATHODE D1
- 4) ANODE D1
- 5) ANODE D1
- 6) COLLECTOR Q1

R0 (06-October 2004)