


SURFACE MOUNT POSITIVE ADJUSTABLE 1.0 AMP VOLTAGE REGULATOR



**Isolated Hermetic Surface Mount Package
1.0 Amp, Positive Adjustable Voltage
Regulator**

FEATURES

- Hermetic Isolated Surface Mount Package
- Adjustable Output Voltage
- Eliminates Stocking Fixed Voltages
- Built-In Thermal Overload Protection
- Short Circuit Current Limiting
- Product Is Available Hi-Rel Screened
- Electrically Similar To Industry Standard P/N LM117

DESCRIPTION

This three terminal positive regulator is supplied in a hermetically sealed metal surface mount package. All protective features are designed into the circuit, including thermal shutdown, current limiting and safe-area control. With heat sinking, they can deliver over 1.0 amp of output current. This unit features output voltages that can be trimmed using external resistors, from 1.2 volts to 37 volts.

ABSOLUTE MAXIMUM RATINGS

Input to Output Voltage Differential	405 V
Operating Junction Temperature Range	- 55°C to + 150°C
Storage Temperature Range	- 55°C to + 150°C
Typical Power/Thermal Characteristics:	
Rated Power @ 25°C	
T _C	17.5W
T _A	3W
Thermal Resistance:	
θ _{JC}	3.5°C/W
θ _{JA}	42°C/W
Lead Temperature at Case (5 sec)	225°C

3.5

ELECTRICAL CHARACTERISTICS -55°C T_A 125°C, I_L = 8mA (unless otherwise specified)



Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Reference Voltage	V _{REF}	V _{DIFF} = 3.0V, T _A = 25°C	1.20	1.30	V
		V _{DIFF} = 3.3V	1.20	1.30	
		V _{DIFF} = 40V	1.20	1.30	
Line Regulation (Note 1)	R _{LINE}	3.0V V _{DIFF} 40V, V _{out} = V _{ref} , T _A = 25°C	-9	9	mV
		3.3V V _{DIFF} 40V, V _{out} = V _{ref}	-23	23	
Load Regulation (Note 1)	R _{LOAD}	V _{DIFF} = 3.0V, 10mA I _L 1.5A, T _A = 25°C	-15	15	mV
		V _{DIFF} = 3.3V, 10mA I _L 1.5A	-15	15	
		V _{DIFF} = 40V, 10mA I _L 300mA, T _A = 25°C	-15	15	
		V _{DIFF} = 40V, 10mA I _L 195mA	-15	15	
Thermal Regulation	V _{RTH}	V _{in} = 14.6V, I _L = 1.5A	-16	16	mV
		P _d = 20 Watts, t = 20 ms, T _A = 25°C			
Ripple Rejection (Note 2)	R _N	f = 120 Hz, V _{out} = V _{ref} C _{Adj} = 10 μF, I _{out} = 100 mA	66		dB
Adjustment Pin Current	I _{Adj}	V _{DIFF} = 3.0V, T _A = 25°C		100	μA
		V _{DIFF} = 3.3V		100	
		V _{DIFF} = 40V		100	
Adjustment Pin Current Change	I _{Adj}	V _{DIFF} = 3.0V, 10mA I _L 1.5A, T _A = 25°C	-5	5	μA
		V _{DIFF} = 3.3V, 10mA I _L 1.5A	-5	5	
		V _{DIFF} = 40V, 10mA I _L 300mA, T _A = 25°C	-5	5	
		V _{DIFF} = 40V, 10mA I _L 195mA	-5	5	
		3.0V V _{DIFF} 40V, T _A = 25°C	-5	5	
		3.3V V _{DIFF} 40V	-5	5	
Miminum Load Current	I _{Lmin}	V _{DIFF} = 3.0V, V _{OUT} = 1.4V (forced)		5.0	mA
		V _{DIFF} = 3.3V, V _{OUT} = 1.4V (forced)		5.0	
		V _{DIFF} = 40V, V _{OUT} = 1.4V (forced)		5.0	
Current Limit (Note 2)	I _{CL}	V _{DIFF} = 15V	1.5	3.5	A
		V _{DIFF} = 40V, T _A = 25°C	0.18	1.5	

- Notes:**
1. Load and Line Regulation are specified at a constant junction temperature. Pulse testing with low duty cycle is used. Changes in output voltage due to heating effects must be taken into account separately.
 2. If not tested, shall be guaranteed to the specified limits.
 3. The • denotes the specifications which apply over the full operating temperature range.

MECHANICAL OUTLINE

PIN CONNECTION

3.5



Pin 1: V_{OUT}
Pin 2: Adjust
Pin 3: V_{IN}
Case: Isolated