



## Power Schottky Rectifier with common cathode

**I<sub>FAV</sub>** = 2x15 A  
**V<sub>RRM</sub>** = 45 V  
**V<sub>F</sub>** = 0.57 V

| V <sub>RSM</sub><br>V | V <sub>RRM</sub><br>V | Type          |
|-----------------------|-----------------------|---------------|
| 45                    | 45                    | DSSK 28-0045A |



A = Anode, C = Cathode , TAB = Cathode

| Symbol                | Conditions   | Maximum Ratings |      |
|-----------------------|--|-----------------|------|
| I <sub>FRMS</sub>     |  | 35              | A    |
| I <sub>FAV</sub>      | T <sub>C</sub> = 160°C; rectangular, d = 0.5                               | 15              | A    |
| I <sub>FAV</sub>      | T <sub>C</sub> = 160°C; rectangular, d = 0.5; per device                   | 30              | A    |
| I <sub>FSM</sub>      | T <sub>VJ</sub> = 45°C; t <sub>p</sub> = 10 ms (50 Hz), sine               | 280             | A    |
| E <sub>AS</sub>       | I <sub>AS</sub> = 15 A; L = 180 µH; T <sub>VJ</sub> = 25°C; non repetitive | 32              | mJ   |
| I <sub>AR</sub>       | V <sub>A</sub> = 1.5 • V <sub>RRM</sub> typ.; f=10 kHz; repetitive         | 1.5             | A    |
| (dv/dt) <sub>cr</sub> |  | 1000            | V/µs |
| T <sub>VJ</sub>       |  | -55...+175      | °C   |
| T <sub>VJM</sub>      |  | 175             | °C   |
| T <sub>stg</sub>      |  | -55...+150      | °C   |
| P <sub>tot</sub>      | T <sub>C</sub> = 25°C  | 105             | W    |
| M <sub>d</sub>        | mounting torque  | 0.4...0.6       | Nm   |
| Weight                | typical  | 2               | g    |

| Symbol                                 | Conditions  | Characteristic Values |                |
|--|---|-----------------------|----------------|
|  |   | typ.                  | max.           |
| I <sub>R</sub> ①                       | T <sub>VJ</sub> = 25°C; V <sub>R</sub> = V <sub>RRM</sub><br>T <sub>VJ</sub> = 125°C; V <sub>R</sub> = V <sub>RRM</sub>                           | 0.5<br>5              | mA<br>mA       |
| V <sub>F</sub>                         | I <sub>F</sub> = 15 A; T <sub>VJ</sub> = 125°C<br>I <sub>F</sub> = 15 A; T <sub>VJ</sub> = 25°C<br>I <sub>F</sub> = 30 A; T <sub>VJ</sub> = 125°C | 0.57<br>0.67<br>0.69  | V<br>V<br>V    |
| R <sub>thJC</sub><br>R <sub>thCH</sub> |   | 0.5                   | 1.4 K/W<br>K/W |

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %  
Data according to IEC 60747 and per diode unless otherwise specified.

### Features

- International standard package
- Very low V<sub>F</sub>
- Extremely low switching losses
- Low I<sub>RM</sub>-values
- Epoxy meets UL 94V-0

### Applications

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

### Advantages

- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Low losses

Dimensions see Outlines.pdf




Fig. 1 Maximum forward voltage drop characteristics




Fig. 2 Typ. value of reverse current  $I_R$  versus reverse voltage  $V_R$




Fig. 3 Typ. junction capacitance  $C_T$  versus reverse voltage  $V_R$




Fig. 4 Average forward current  $I_{F(AV)}$  versus case temperature  $T_C$




Fig. 5 Forward power loss characteristics




Fig. 6 Transient thermal impedance junction to case at various duty cycles

Note: All curves are per diode