

Plug-In

Power Splitter/Combiner

PSCQ-2-120

2 Way-90° 50Ω 80 to 120 MHz


Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.

Pin Connections

SUMPORT	1
PORT 1 (+90°)	2
PORT 2 (0°)	5
GROUND	3,4,7,8
CASE GROUND	3,4,7,8
50 OHM TERM EXTERNAL	6

Outline Drawing



Outline Dimensions (inch)

A	B	C	D	E	F
.770	.800	.385	.400	.370	.400
19.56	20.32	9.78	10.16	9.40	10.16
G	H	J	K	wt	
.200	.20	.14	.031	grams	
5.08	5.08	3.56	0.79	5.2	

Features

- low insertion loss, 0.3 dB typ.
- good isolation, 25 dB typ.
- rugged shielded case

Applications

- modulators
- balanced amplifiers



CASE STYLE: A01




PRICE: \$28.20 ea. QTY. (1-9)

Splitter Electrical Specifications


FREQ. RANGE (MHz)	ISOLATION (dB)	INSERTION LOSS (dB) Avg. of Coupled Outputs less 3 dB	PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)
f_L - f_U	Typ. Min.	Typ. Max.	Max.	Max.
80-120	25 18	0.3 0.7	3	1.5

Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1 S-2						
80.00	3.54 2.82	0.72	24.60	90.06	1.15	1.13	1.16
81.00	3.50 2.86	0.65	24.52	90.05	1.15	1.13	1.16
83.00	3.44 2.91	0.52	24.39	90.10	1.15	1.13	1.16
85.00	3.36 2.98	0.38	24.27	90.20	1.15	1.13	1.16
87.00	3.30 3.02	0.27	24.13	90.21	1.15	1.13	1.16
90.00	3.21 3.11	0.10	23.93	90.29	1.15	1.13	1.16
93.00	3.14 3.18	0.04	23.72	90.32	1.15	1.13	1.17
96.00	3.07 3.24	0.17	23.50	90.40	1.15	1.14	1.17
99.00	3.01 3.31	0.30	23.29	90.50	1.15	1.14	1.17
102.00	2.97 3.36	0.39	23.06	90.55	1.15	1.14	1.18
106.00	2.92 3.42	0.50	22.74	90.71	1.15	1.15	1.19
110.00	2.90 3.47	0.58	22.41	90.88	1.16	1.15	1.20
114.00	2.89 3.51	0.63	22.07	91.08	1.16	1.16	1.21
118.00	2.88 3.54	0.66	21.70	91.25	1.17	1.17	1.22
120.00	2.89 3.55	0.66	21.50	91.37	1.17	1.17	1.22



electrical schematic



Mini-Circuits®

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

REV. OR
M94664
PSCQ-2-120
HY/TD/CP
060821