

Plug-In

# Power Splitter/Combiner

2 Way-90° 50Ω 14 to 30 MHz

PSCQ-2-26+  
PSCQ-2-26



CASE STYLE: A01

PRICE: \$28.20 ea. QTY. (1-9)

+ RoHS compliant in accordance  
with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site  
for RoHS Compliance methodologies and qualifications.

## Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.

## Pin Connections

SUMPORT	1
PORT 1 (+90°)	2
PORT 2 (0°)	5
GROUND	3,4,7,8
CASE GROUND	3,4,7,8
50 OHM TERM EXTERNAL	6

## Features

- low insertion loss, 0.4 dB typ.
- good isolation, 25 dB typ.
- excellent VSWR, 1.15:1 typ.
- rugged shielded case


## Applications

- modulators
- balanced amplifiers

## Splitter Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)	INSERTION LOSS (dB) Avg. of Coupled Outputs less 3 dB	PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)
$f_L$ - $f_U$	Typ. Min.	Typ. Max.	Max.	Max.
14-30	25 20	0.4 0.7	3	1.5

## Outline Drawing






## Outline Dimensions (inch/mm)


A	B	C	D	E	F
.770	.800	.385	.400	.370	.400
19.56	20.32	9.78	10.16	9.40	10.16
G	H	J	K	wt	
.200	.20	.14	.031	grams	
5.08	5.08	3.56	0.79	5.2	

## Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1 S-2						
14.00	3.94 2.53	1.41	39.77	89.46	1.03	1.04	1.02
14.40	3.83 2.61	1.22	39.95	89.49	1.03	1.05	1.02
15.20	3.65 2.76	0.89	40.33	89.50	1.03	1.05	1.02
16.00	3.49 2.91	0.58	40.81	89.57	1.04	1.05	1.02
17.20	3.29 3.10	0.19	41.79	89.55	1.04	1.05	1.02
18.40	3.14 3.28	0.14	43.06	89.62	1.04	1.05	1.02
19.60	3.02 3.42	0.40	44.86	89.68	1.04	1.06	1.02
20.80	2.94 3.54	0.60	47.48	89.77	1.05	1.06	1.02
22.00	2.88 3.62	0.74	50.42	89.86	1.05	1.06	1.03
23.60	2.86 3.70	0.84	48.51	90.03	1.06	1.07	1.03
25.20	2.89 3.72	0.83	42.61	90.29	1.07	1.08	1.04
26.80	2.98 3.67	0.69	37.92	90.63	1.08	1.09	1.05
28.40	3.14 3.58	0.43	34.01	91.08	1.10	1.10	1.06
29.60	3.33 3.46	0.13	31.47	91.54	1.12	1.11	1.07
30.00	3.40 3.42	0.02	30.67	91.70	1.13	1.12	1.07



## electrical schematic



**Mini-Circuits®**

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

REV. A  
M98898  
PSCQ-2-26  
HY/TD/CP/AM  
060821