

## M6 SERIES P10TG-XXXXZ2:1H35M 3.5 KV ISOLATED 2 W REGULATED DUAL OUTPUT DIP24

### Available Inputs:

12, 24 and 48 VDC Wide Input 2:1

### Available Outputs:

(+/-)3.3, 12, 15 and 18 VDC

Other specifications please enquire.

### Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

#### Input Specifications

Voltage range

9 - 18 VDC (12 VDC), 18 - 36 VDC (24 VDC)  
36 - 72 VDC (48 VDC)

Filter

Pi Network

#### Isolation Specifications

Rated voltage

3500 Vdc

Leakage current

1 mA

Resistance

10<sup>9</sup> Ohm

Capacitance

80 pF typ.

#### Output Specifications

Voltage accuracy

+/- 1 % typ. +/-2% max.

Ripple and noise (at 20 MHz BW)

60 mV p-p, max.

Short circuit protection

Continuous , restart automatic

Line voltage regulation

+/- 0,5 % max.

Load voltage regulation

+/- 0,5 % max.

Temperature coefficient

+/- 0,02 % / °C

#### General Specifications

Efficiency

70 % to 85 %

Switching frequency

250 KHz, typ.

#### Environmental Specifications

Operating temperature (ambient)

-40°C to +85°C

Storage temperature

- 55 °C to + 125 °C

Derating

See graph

Humidity

Up to 90 %, non condensing

Cooling

Free air convection

#### Physical Characteristics

Dimensions

31,75 x 20,32 x 10,16 mm

1,25 x 0,80 x 0,40 inches

Weight

16,3 g


Case material

Nickel Coated Copper


### Examples of Partnumbers/Modelcode

PART NO.	INPUT VOLTAGE (VDC) Nominal	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P10TG-1205Z2:1H35M	9-18	17	225	+/- 5	+/- 200	74
P10TG-1212Z2:1H35M	9-18	17	213	+/- 12	+/- 83	78
P10TG-2405Z2:1H35M	18-36	17	109	+/- 5	+/- 200	76
P10TG-4805Z2:1H35M	36-72	15	56	+/- 5	+/- 200	75
P10TG-4812Z2:1H35M	36-72	15	53	+/- 12	+/- 83	79

Dimensions



Derating Graph and Pinning



Specification can be changed without notice.

Copyright PEAK electronics GmbH