


Series 850

PCB connectors 1.27 mm

Single row / double row / triple row


Solder tail






Ultraminiature PCB pin connectors, solder tail

Grid spacing 1.27×1.27 mm

Screw-machined pin Ø 0.43 mm




For corresponding receptacles see pages 10, 11 and 12

Platings	Sleeve 	Clip 	Pin 
10 90			0.25 µm Au 5 µm Sn Pb

Ordering information


Replace **xxx** with the number of poles, e.g. 852-10-**xxx**-10-001
for a double row version with 8 pins per row becomes:
852-10-**016**-10-001



850-10-xxx-10-001
850-90-xxx-10-001

Straight pin connector: solder
tail, single row


Availability from: 1 to 50 contacts
Standard number of contacts 25
and 50



852-10-xxx-10-001
852-90-xxx-10-001

Straight pin connector: solder
tail, double row


Availability from: 4 to 100
contacts
Standard number of contacts 50
and 100



852-10-xxx-10-002
852-90-xxx-10-002

Straight pin connector: solder
tail, double row with 2.54 mm
row to row distance

Availability from: 4 to 100
contacts
Standard number of contacts 100



854-10-xxx-10-001
854-90-xxx-10-001

Straight pin connector: solder
tail, triple row

Availability from: 9 to 150
contacts
Standard number of contacts 150