


Preliminary Data Sheet


Features

- For broadband applications
- Typical 3 dB bandwidth of 10 MHz
- Single-ended or differential operation
- Ceramic Surface Mount Package (SMP)
- Small size




Package

Surface Mount 7.01 x 5.51 x 1.63 mm



Pin Configuration

Bottom View



Pin No.	Description
3	Input
4	Input return
9	Output
10	Output return
1,2,5,6	Case ground
7,8,11,12	Case ground

Dimensions shown are nominal in millimeters
All tolerances are ± 0.15 mm except overall
length and width $+0.13$ mm / -0.13 mm

Body: Al_2O_3 ceramic
Lid: Kovar, Ni plated
Terminations: Au plating 0.5 - 1.0 μ m,
over a 2 - 6 μ m Ni plating

Preliminary Data Sheet

Electrical Specifications ⁽¹⁾

Operating Temperature Range: ⁽²⁾ -10 to +60 °C


Parameter ⁽³⁾	Minimum	Typical	Maximum	Unit
Center Frequency	-	325	-	MHz
Minimum Insertion Loss	-	9.6	14	dB
Lower 3 dB Bandedge ⁽⁴⁾	-	318.99	320	MHz
Upper 3 dB Bandedge	330	332.02	-	MHz
Lower 40 dB Bandedge ⁽⁴⁾	307.5	315.4	-	MHz
Upper 40 dB Bandedge	-	339.1	342.5	MHz
Amplitude Ripple	-	0.6	1.0	dB
Phase Linearity	-	9	-	deg
Group Delay Variation	-	48	75	nsec
Relative Attenuation ⁽⁴⁾				
10 - 220 MHz	50	55	-	dB
220 - 300 MHz	45	50	-	dB
350 - 355 MHz	40	45	-	dB
355 - 375 MHz	35	40	-	dB
375 - 380 MHz	40	45	-	dB
380 - 405 MHz	35	40	-	dB
405 - 500 MHz	40	45	-	dB
Source Impedance: ⁽⁵⁾	-	50	-	Ω
Load Impedance: ⁽⁵⁾	-	50	-	Ω
Substrate Material	-	YZ LiNbO ₃	-	-

Notes:

1. All specifications are based on the test circuit shown below
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. All attenuation measurements are measured relative to minimum insertion loss
5. This is the optimum impedance in order to achieve the performance shown





Test Circuit:

Actual matching values may vary due to PCB layout and parasitics




Preliminary Data Sheet


Typical Performance (at +25°C)



Input Smith Chart




Output Smith Chart




Preliminary Data Sheet

Matching Schematics

Actual matching values may vary due to PCB layout and parasitics




Marking





The date code consists of: day of the current year (Julian, 3 digits), last digit of the year (1 digit) and hour (2 digits)

PCB Footprint



This footprint represents a recommendation only
Dimensions shown are nominal in millimeters

Tape and Reel



Dimensions shown are nominal in millimeters
Packaging quantity: 3000 units/reel

Preliminary Data Sheet

Maximum Ratings

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating Temperature Range	T	-10	+25	+60	°C
Storage Temperature Range	T _{stg}	-40	-	+85	°C

Warnings

- Electrostatic Sensitive Device (ESD)
- Avoid ultrasonic exposure



Links to Additional Technical Information

[PCB Layout Tips](#)[Qualification Flowchart](#)[Soldering Profile](#)[S-Parameters](#)[Other Technical Information](#)

Sawtek's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. Sawtek does not accept any liability for applications, processes, circuits or assemblies which are implemented using any Sawtek component described in this data sheet.

Contact Information



PO Box 609501
Orlando, FL 32860-9501
USA

Phone: +1 (407) 886-8860
Fax: +1 (407) 886-7061
Email: custservice@sawtek.com
Web: www.sawtek.com

Or contact one of our worldwide
network of [sales offices](#),
[representatives or distributors](#)